

Transformadores de protección y medida para baja tensión

TRANSFORMADORES TOROIDALES

- Hasta 1200 A de primario .
- Relación de transformación .../5.
- Cubre bornas, base de anclaje, sujetapletinas y fijación sobre carril DIN incluidos.
- Normativa: IE C 60044-1 , BS 2627.

Primario .../ 5A	Modelo	Código	VA clase		
			0,5	1	3
100	CT20N	41380	-	2,5	2,5
150	CT20N	41381	-	2,5	3,75
200	CT20N	41382	2,5	5	5
250	CT20N	41383	3,75	5	7,5
300	CT20N	41384	3,75	5	7,5
400	CT20N	41385	5	5	5
500	CT20N	41386	2,5	3,75	5
600	CT20N	41387	5	5	7,5

CARACTERÍSTICAS	
Sobrecarga permanente	1,2 I _n
Tensión de servicio: pletina / cable 1000V	660V / 1000V
Frecuencia	50 / 60 Hz
Bornas cortocircuitables en secundario abierto	YES
Tensión asignada máxima Um	0,72 kV
Tensión soportada a frecuencia industrial	3 kV

CT




Cubre bornas



CE

DIAGRAMA DE CONEXIONES

$$I_s = \frac{I_n \text{ motor}}{I_n \text{ CT}} \times 5 \times n$$



DIMENSIONES CT (mm)

